DATA SHEET FOR

TRANSFORMER # U1507

Made for STANDARD

LEADS			SCHEMATIC			LEADS
S#18/8"	0V	WHITE		BLUE	0V	S#10/8"
N/R THERMAL FUSE 121°C					UO = 12.5V RMS	
S#18/8"	120V	BLACK		YELLOW	11.8V RMS / 300VA	S#10/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 2.68A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 48°C

DIMENSIONS/WEIGHT:	MOUNTING:	CORE DATA:
OD = 5.0"	ONE WASHER/TWO PADS 110mm	CORE # 900280
H = 2.0"	THICKNESS = 0.08"	CORE LOSS = 1.3 W
WEIGHT = 5.5 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD CURRENT = 27 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliant.Class B insulation.

Label:

Transformer # U1507
INPUT: 120V 60Hz WHT-BLK
OUTPUT: 11.8V / 300W BLU-YEL

(Logo)

(date code)

SPEC DATE: 12/17/20

By: mx

TOROID CORPORATION

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302
e-mail: sales@toroid.com * web: www.toroid.com