



DATA SHEET FOR
AUTO-TRANSFORMER # A5615

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#22/8"	COMMON	WHITE	
S#22/8"	120V input	BLACK	
S#22/8"	230V/250VA	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 2.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 45 °C

DIMENSIONS/WEIGHT:

OD = 3.9"
H = 1.7"
WEIGHT = 2.6 LBS.

MOUNTING:

WASHER/PADS = 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 900115
CORE LOSS = 0.7 W
NO-LOAD CURRENT = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CUL certified to CSA C22.2 No. 66 standards. Class B insulation. RoHS compliant.

Label:



Auto-Transformer # A5615
Input: 120Vac 60Hz blk-wht
Output: 230V 250VA brn-wht

SPEC DATE: 07/07/20

(Logo)

By: *mx*

(date code)

TOROID CORPORATION