



DATA SHEET FOR
 AUTO-TRANSFORMER # A5618

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#16/8"	COMMON	WHITE	
S#16/8"	120V input	BLACK	
S#16/8"	230V/1000VA	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
 RATED PRIMARY CURRENT: 8.7A
 RATED FREQUENCY: 60 Hz
 TEMP. RISE AT RATED LOAD: 63 °C

DIMENSIONS/WEIGHT:

OD = 5.5"
 H = 2.3"
 WEIGHT = 7.1 LBS.

MOUNTING:

WASHER/PADS = 110mm
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.32"

CORE DATA:

CORE # 900491
 CORE LOSS = 2.0 W
 NO-LOAD CURRENT = 43 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CUL certified to CSA C22.2 No. 66 standards. Class B insulation. RoHS compliant.

Label:



Auto-Transformer # A5618
 Input: 120Vac 60Hz blk-wht
 Output: 230V 1000VA brn-wht

SPEC DATE: 12/17/20

(Logo)

By: *mx*

(date code)

TOROID CORPORATION