



DATA SHEET FOR
 AUTO-TRANSFORMER # A5620

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#22/8"	COMMON	WHITE	
S#22/8"	120V/250VA	BLACK	
S#22/8"	230V IN	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%
 RATED PRIMARY CURRENT: 1.2A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 54°C

DIMENSIONS/WEIGHT:

OD = 3.7"
 H = 1.8"
 WEIGHT = 2.6 LBS.

MOUNTING:

WASHER/PADS = 70mm
 THICKNESS = 0.05"
 HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 120
 CORE LOSS = 0.7W
 NO-LOAD CURRENT = 7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:



Auto-Transformer # A5620
 INPUT: 230VAC 50/60Hz BRN-WHT
 OUTPUT: 120V 250VA BLK-WHT

SPEC DATE: 12/17/20

(Logo)

By: *MX/LL*

(date code)

TOROID CORPORATION