



DATA SHEET FOR
AUTO-TRANSFORMER # A5620

Made for STANDARD

LEADS

SCHEMATIC

LEADS

| | | | |
|---------|------------|-------|--|
| S#22/8" | COMMON | WHITE | |
| S#22/8" | 120V/250VA | BLACK | |
| S#22/8" | 230V IN | BROWN | |

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%
RATED PRIMARY CURRENT: 1.2A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 54°C

DIMENSIONS/WEIGHT:
OD = 3.7"
H = 1.8"
WEIGHT = 2.6 LBS.

MOUNTING:
WASHER/PADS = 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 120
CORE LOSS = 0.7W
NO-LOAD CURRENT = 7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:



SPEC DATE: 07/07/20

Auto-Transformer # A5620
INPUT: 230VAC 50/60Hz BRN-WHT
OUTPUT: 120V 250VA BLK-WHT

(Logo)

By: *MX/LL*

(date code)

TOROID CORPORATION