



DATA SHEET FOR  
TRANSFORMER # A5621

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#18/8"	230V INPUT	BROWN	
S#18/8"	120V/500VA	BLACK	
S#18/8"	COMM.	WHITE	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%  
RATED PRIMARY CURRENT: 2.3A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 50 °C

DIMENSIONS/WEIGHT:  
OD = 4.5"  
H = 2.2"  
WEIGHT = 4.8 LBS.

MOUNTING:  
WASHER/PADS = 90mm  
THICKNESS = 0.06"  
HOLE DIAMETER = 0.25"

CORE DATA:  
CORE # 900240  
CORE LOSS = 1.3 W  
NO-LOAD CURRENT = 13 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:



SPEC DATE: 12/17/20

Auto-Transformer # A5621  
INPUT: 230VAC 50/60Hz BRN-WHT  
OUTPUT: 120V 500VA BLK-WHT

(Logo)

By: *mx/LL*

(date code)

**TOROID CORPORATION**