



DATA SHEET FOR  
 AUTO-TRANSFORMER # A5622

STANDARD

LEADS

SCHEMATIC

LEADS

S#18/8"	230V IN	BROWN	
S#18/8"	120V/750VA	BLACK	
S#18/8"	COMM.	WHITE	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%  
 RATED PRIMARY CURRENT: 3.4A  
 RATED FREQUENCY: 50/60 Hz  
 TEMP. RISE AT RATED LOAD: 54 °C

DIMENSIONS/WEIGHT:  
 OD = 5.5"  
 H = 2.1"  
 WEIGHT = 6.5 LBS.

MOUNTING:  
 WASHER/PADS = 110mm  
 THICKNESS = 0.08"  
 HOLE DIAMETER = 0.32"

CORE DATA:  
 CORE # 900370  
 CORE LOSS = 1.7 W  
 NO-LOAD CURRENT = 17 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:



SPEC DATE: 12/17/20

Auto-Transformer # A5622  
 INPUT: 230VAC 50/60Hz BRN-WHT  
 OUTPUT: 120V 750VA BLK-WHT

(Logo)

By: *MX/LL*

(date code)

**TOROID CORPORATION**