

DATA SHEET FOR  
AUTO-TRANSFORMER # A5622

STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>	<u>LEADS</u>
S#18/8"	230V IN	BROWN	
S#18/8"	120V/750VA	BLACK	
S#18/8"	COMM.	WHITE	


LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%  
RATED PRIMARY CURRENT: 3.4A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 54 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.5"	WASHER/PADS = 110mm	CORE # 900370
H = 2.1"	THICKNESS = 0.08"	CORE LOSS = 1.7 W
WEIGHT = 6.5 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD CURRENT = 17 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:  Auto-Transformer # A5622  
 INPUT: 230VAC 50/60Hz BRN-WHT  
 OUTPUT: 120V 750VA BLK-WHT

By: *mx/LL* (date code)

SPEC DATE: 07/07/20  
(Logo)

**TOROID CORPORATION**