



DATA SHEET FOR  
TRANSFORMER # 602.122

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#22/8"
S#22/8"	117V	WHITE		RED	12V RMS / 1.00A RMS	M#22/8"
				ORANGE	0V	M#22/8"
				YELLOW	12V RMS / 1.00A RMS	M#22/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 0.3A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 60 °C

DIMENSIONS/WEIGHT:  
OD = 2.4"  
H = 1.2"  
WEIGHT = 0.8 LBS.

MOUNTING:  
WASHER/PADS = 50mm  
THICKNESS = 0.04"  
HOLE DIAMETER = 0.17"

CORE DATA:  
CORE # 15  
CORE LOSS = 0.2 W  
NO-LOAD CURRENT = 4 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label: Transformer # 602.122 (U2004)  
SPEC DATE: 12/18/20 PRIM. 117V 60Hz BK(WH-WH)  
(Logo) SEC. 2x12V/1.00A BR-RD/OR-YE  
By: *MX/LL* (date code)

**TOROID CORPORATION**