



DATA SHEET FOR  
TRANSFORMER # 602.152

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	S#22/8"
S#22/8"	117V	WHITE		RED	15V RMS / 0.80A RMS	S#22/8"
				ORANGE	0V	S#22/8"
				YELLOW	15V RMS / 0.80A RMS	S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.  
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 0.3A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 61°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.4"	WASHER/PADS = 50mm	CORE # 15
H = 1.2"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 0.7 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 602.152 (U2005)  
Prim. 117V 60Hz bk+(wh-wh)  
Sec. 2x15V/0.80A br-re/or-yel

SPEC DATE: 12/18/20

(Logo) (date code)

By: *MX/LL*

**TOROID CORPORATION**