



DATA SHEET FOR  
TRANSFORMER # 602.182

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#22/8"      0V		BROWN      0V
S#22/8"      117V		RED      18V RMS / 0.67A RMS  ORANGE      0V YELLOW      18V RMS / 0.67A RMS
		UO = 23.2V RMS UO = 23.2V RMS
		S#22/8" S#22/8" S#22/8" S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.  
 LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

-----  
 NOMINAL SUPPLY:            117V +/-10%  
 RATED PRIMARY CURRENT: 0.3A  
 RATED FREQUENCY:        60 Hz  
 TEMP. RISE AT RATED LOAD: 64°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.4"	WASHER/PADS = 50mm	CORE # 15
H = 1.2"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 0.7 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

SPEC DATE: 12/18/20	Label: Transformer # 602.182 (U2006)	
	Prim. 117V 60Hz bk+(wh-wh)	
	Sec. 2x18V/0.67A br-re/or-yel	
By: <i>MX/LL</i>	(Logo)	(date code)

**TOROID CORPORATION**