

DATA SHEET FOR
TRANSFORMER # 602.182

Made for STANDARD

LEADS		SCHEMATIC		LEADS		
S#22/8"	0V	WHITE		BROWN	0V	S#22/8"
S#22/8"	117V	WHITE		RED	18V RMS / 0.67A RMS	S#22/8"
				ORANGE	0V	S#22/8"
				YELLOW	18V RMS / 0.67A RMS	S#22/8"


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.3A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 64°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.4"	WASHER/PADS = 50mm	CORE # 15
H = 1.2"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 0.7 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label:  Transformer # 602.182 (U2006)
 Prim. 117V 60Hz bk+(wh-wh)
 Sec. 2x18V/0.67A br-re/or-yel

SPEC DATE: 09/20/18

(Logo) (date code)

By: *MX/LL*

TOROID CORPORATION