



DATA SHEET FOR
TRANSFORMER # 604.082

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#20/8"
S#22/8"	117V	WHITE		RED	8.5V RMS / 2.47A RMS	M#20/8"
				ORANGE	0V	M#20/8"
				YELLOW	8.5V RMS / 2.47A RMS	M#20/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.4A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 63 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 604.082 (U2008)
SPEC DATE: 12/18/20 PRIM. 117V 60Hz bk+(wh-wh)
(Logo) SEC. 2x8.5V/2.47A br-re/or-ye
By: *MX/LL* (date code)

TOROID CORPORATION