



DATA SHEET FOR  
TRANSFORMER # 604.122

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#22/8"	0V	WHITE		BROWN	0V	M#21/8"	
						UO = 14.6V RMS	
S#22/8"	117V	WHITE			RED	12V RMS / 1.75A RMS	M#21/8"
					ORANGE	0V	M#21/8"
					UO = 14.6V RMS		
				YELLOW	12V RMS / 1.75A RMS	M#21/8"	

PRIMARIES ARE INSIDE A SLEEVE.  
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 0.4A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 60 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 604.122 (U2009)  
SPEC DATE: 12/18/20 PRIM. 117V 60HZ BK+(WH-WH)  
(Logo) SEC. 2x12V/1.75A BN-RE/OR-YE  
By: *MX/LL* (date code)

**TOROID CORPORATION**