



DATA SHEET FOR  
TRANSFORMER # 604.152

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#22/8"
S#22/8"	117V	WHITE		RED	15V RMS / 1.40A RMS	M#22/8"
				ORANGE	0V	M#22/8"
				YELLOW	15V RMS / 1.40A RMS	M#22/8"

PRIMARIES ARE INSIDE A SLEEVE.  
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 0.4A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 61°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 604.152 (U2011)  
SPEC DATE: 12/18/20 PRIM. 117V 60HZ BK+(WH-WH)  
SEC. 2x15V/1.40A BN-RE/OR-YE  
(Logo) (date code)

By: *MX/LL*

**TOROID CORPORATION**