



DATA SHEET FOR
TRANSFORMER # 604.182

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#23/8"
S#22/8"	117V	WHITE		RED	18V RMS / 1.17A RMS	M#23/8"
				ORANGE	0V	M#23/8"
				YELLOW	18V RMS / 1.17A RMS	M#23/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.4A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 64°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 604.182 (U2012)
PRIM. 117V 60HZ BK+(WH-WH)
SEC. 2x18V/1.17A BN-RE/OR-YE

SPEC DATE: 12/18/20

(Logo)

By: *MX/LL* (date code)

TOROID CORPORATION