



DATA SHEET FOR
TRANSFORMER # 604.242

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8" 0V	WHITE		BROWN	0V	M#24/8"
S#22/8" 117V	WHITE		RED	24V RMS / 0.88A RMS	M#24/8"
			ORANGE	0V	M#24/8"
			YELLOW	24V RMS / 0.88A RMS	M#24/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.4A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 61 °C

DIMENSIONS/WEIGHT:
OD = 2.8"
H = 1.3"
WEIGHT = 1.1 LBS.

MOUNTING:
WASHER/PADS = 50mm
THICKNESS = 0.04"
HOLE DIAMETER = 0.17"

CORE DATA:
CORE # 30
CORE LOSS = 0.2 W
NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:
SPEC DATE: 12/18/20

Transformer # 604.242 (U2013)
PRIM. 117V 60Hz BK(WH-WH)
SEC. 2x24V/0.88A BR-RD/OR-YE
(Logo) (date code)



By: *MX/LL*

TOROID CORPORATION