



DATA SHEET FOR
TRANSFORMER # 607.152

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#25/8"	0V	WHITE	┌	└	BROWN	0V		M#20/8"
							UO = 17.4V RMS	
M#25/8"	117V	WHITE	└	┌	RED	15V RMS / 2.07A RMS		M#20/8"
					ORANGE	0V	UO = 17.4V RMS	M#20/8"
					YELLOW	15V RMS / 2.07A RMS		M#20/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.7A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 57°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.2"	WASHER/PADS = 60mm	CORE # 50
H = 1.4"	THICKNESS = 0.05"	CORE LOSS = 0.4 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.2"	NO-LOAD CURRENT = 9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL 1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label:



Transformer # 607.152 (U2016)
Prim. 117V 60Hz bk+(wh-wh)
Sec. 2x15V/2.07A bn-re/or-ye

SPEC DATE: 12/18/20

(Logo)

By: *MX/LL*

(date code)

TOROID CORPORATION