

DATA SHEET FOR
TRANSFORMER # 607.182

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#25/8"	0V	WHITE		BROWN	0V	M#22/8"
M#25/8"	117V	WHITE		RED	18V RMS / 1.72A RMS	M#22/8"
				ORANGE	0V	M#22/8"
				YELLOW	18V RMS / 1.72A RMS	M#22/8"
				UO = 21.3V RMS		
				UO = 21.3V RMS		


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.7A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 57 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.2"	WASHER/PADS = 60mm	CORE # 50
H = 1.4"	THICKNESS = 0.05"	CORE LOSS = 0.4 W
WEIGHT = 1.1 LBS.	HOLE DIAMETER = 0.2"	NO-LOAD CURRENT = 9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL 1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label:  Transformer # 607.182 (U2017)
 SPEC DATE: 12/18/20 Prim. 117V 60Hz bk+(wh-wh)
 (Logo) Sec. 2x18V/1.72A bn-re/or-ye
 By: *MX/LL* (date code)

TOROID CORPORATION