

DATA SHEET FOR  
TRANSFORMER # 636.220

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#17/8"	0V	WHITE		BROWN	0V	M#20/8"
M#17/8"	117V	WHITE		BROWN	220V RMS / 1.69A RMS	M#20/8"


PRIMARIES ARE INSIDE A SLEEVE.  
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 3.2A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 59 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90mm	CORE # 900300
H = 2.3"	THICKNESS = 0.06"	CORE LOSS = 1.5 W
WEIGHT = 5.7 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 34 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:   
Transformer # 636.220 (U2036)  
PRIM. 117V 60Hz BK(WH-WH)  
SEC. 220V/1.59A BR-BR  
SPEC DATE: 12/18/20  
(Logo)  
By: *MX/LL* (date code)

**TOROID CORPORATION**

2020 Northwood Drive \* Salisbury, MD 21801 \* Tel: 410-860-0300 \* Fax: 410-860-0302  
e-mail: sales@toroid.com \* web: www.toroid.com