

ISO 9001
Certified

DATA SHEET FOR
TRANSFORMER # 636.220

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#17/8"	0V	WHITE		BROWN	0V	M#20/8"
M#17/8"	117V	WHITE		BROWN	220V RMS / 1.69A RMS	M#20/8"

UO = 234.0V RMS

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 3.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 59 °C


DIMENSIONS/WEIGHT:
OD = 4.5"
H = 2.3"
WEIGHT = 5.7 LBS.

MOUNTING:
WASHER/PADS = 90mm
THICKNESS = 0.06"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 900300
CORE LOSS = 1.5 W
NO-LOAD CURRENT = 34 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 636.220 (U2036)
 SPEC DATE: 09/20/18 PRIM. 117V 60Hz BK (WH-WH)
 (Logo) SEC. 220V/1.59A BR-BR
 By: *MX/LL* (date code)

TOROID CORPORATION