


ISO 9001
Certified

DATA SHEET FOR
TRANSFORMER # 660.220

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#15/8"	0V	WHITE		BROWN	0V	M#18/8"
M#15/8"	117V	WHITE		BROWN	220V RMS / 2.60A RMS	M#18/8"

UO = 231.5V RMS

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.1A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 61 °C

DIMENSIONS/WEIGHT:
OD = 5.5"
H = 2.4"
WEIGHT = 8.1 LBS.

MOUNTING:
WASHER/PADS = 110mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.32"

CORE DATA:
CORE # 500
CORE LOSS = 2.3 W
NO-LOAD CURRENT = 52 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

SPEC DATE: 09/20/18

By: *MX/LL*

Label:

(Logo)



Transformer # 660.220 (U2043)
PRIM. 117V 60Hz BK(WH-WH)
SEC. 220V/2.60A BRN-BRN

(date code)

TOROID CORPORATION