

ISO 9001
Certified

DATA SHEET FOR
TRANSFORMER # 660.242

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
M#15/8"	0V	WHITE		BROWN	0V	M#11/8"	
M#15/8"	117V	WHITE		RED	24V RMS / 12.5A RMS	M#11/8"	
				ORANGE	0V	M#11/8"	
				YELLOW	24V RMS / 12.5A RMS	M#11/8"	

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
 RATED PRIMARY CURRENT: 5.2A
 RATED FREQUENCY: 60 Hz
 TEMP. RISE AT RATED LOAD: 60 °C


DIMENSIONS/WEIGHT:
 OD = 5.5"
 H = 2.4"
 WEIGHT = 8.1 LBS.

MOUNTING:
 WASHER/PADS = 110mm
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.32"

CORE DATA:
 CORE # 500
 CORE LOSS = 2.3 W
 NO-LOAD CURRENT = 52 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 660.242 (U2037)
 SPEC DATE: 09/20/18 PRIM. 117V 60Hz BK(WH-WH)
 (Logo) SEC. 2x24V/12.5A BR-RD/OR-YE
 By: *MX/LL* (date code)

TOROID CORPORATION