

ISO 9001
Certified

DATA SHEET FOR
TRANSFORMER # 660.302

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#15/8"	0V	WHITE		BROWN	0V	M#12/8"
M#15/8"	117V	WHITE		RED	30V RMS / 10.0A RMS	M#12/8"
				ORANGE	0V	M#12/8"
				YELLOW	30V RMS / 10.0A RMS	M#12/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C


DIMENSIONS/WEIGHT:
OD = 5.5"
H = 2.4"
WEIGHT = 8.1 LBS.

MOUNTING:
WASHER/PADS = 110mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.32"

CORE DATA:
CORE # 500
CORE LOSS = 2.3 W
NO-LOAD CURRENT = 52 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 660.302 (U2038)
SPEC DATE: 09/20/18 PRIM. 117V 60Hz BK(WH-WH)
(Logo) SEC. 2x30V/10.0A BR-RD/OR-YE
By: *MX/LL* (date code)

TOROID CORPORATION

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302
e-mail: sales@toroid.com * web: www.toroid.com