



DATA SHEET FOR
TRANSFORMER # 660.382

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
M#15/8"	0V	WHITE		BROWN	0V	M#13/8"
M#15/8"	117V	WHITE		RED	38V RMS / 7.76A RMS	M#13/8"
				ORANGE	0V	M#13/8"
				YELLOW	38V RMS / 7.76A RMS	M#13/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.3A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.5"	WASHER/PADS = 112mm	CORE # 500
H = 2.4"	THICKNESS = 0.08"	CORE LOSS = 2.3 W
WEIGHT = 8.1 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD CURRENT = 53 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label: Transformer # 660.382 (UL2041)
SPEC DATE: 12/18/20 PRIM. 117V 60HZ BK+(WH-WH)
(Logo) SEC. 2x38V/7.76A BN-RE/OR-YE
By: *MX/LL* (date code)

TOROID CORPORATION