

DATA SHEET FOR
TRANSFORMER # 660.382

Made for STANDARD

| LEADS | | SCHEMATIC | | LEADS | | |
|---------|------|-----------|--|--------|---------------------|---------|
| M#15/8" | 0V | WHITE | | BROWN | 0V | M#13/8" |
| M#15/8" | 117V | WHITE | | RED | 38V RMS / 7.76A RMS | M#13/8" |
| | | | | ORANGE | 0V | M#13/8" |
| | | | | YELLOW | 38V RMS / 7.76A RMS | M#13/8" |


PRIMARYS ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.3A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C

| | | |
|---------------------------|-----------------------|-------------------------|
| <u>DIMENSIONS/WEIGHT:</u> | <u>MOUNTING:</u> | <u>CORE DATA:</u> |
| OD = 5.5" | WASHER/PADS = 112mm | CORE # 500 |
| H = 2.4" | THICKNESS = 0.08" | CORE LOSS = 2.3 W |
| WEIGHT = 8.1 LBS. | HOLE DIAMETER = 0.32" | NO-LOAD CURRENT = 53 mA |

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label:  Transformer # 660.382 (UL2041)
 SPEC DATE: 09/20/18 PRIM. 117V 60HZ BK+(WH-WH)
 SEC. 2x38V/7.76A BN-RE/OR-YE
 (Logo) (date code)

By: *MX/LL*

TOROID CORPORATION