



DATA SHEET FOR
TRANSFORMER # 699.502

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#12/8"	0V	WHITE		BROWN	0V	M#12/8"
M#12/8"	117V	WHITE		RED	50V RMS / 10.0A RMS	M#12/8"
				ORANGE	0V	M#12/8"
				YELLOW	50V RMS / 10.0A RMS	M#12/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 8.9A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:

OD = 6.3"
H = 2.4"
WEIGHT = 12.4 LBS.

MOUNTING:

WASHER/PADS = 145mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.40"

CORE DATA:

CORE # 800
CORE LOSS = 3.5 W
NO-LOAD CURRENT = 84 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

SPEC DATE: 12/18/20

By: *MX/LL*

Label:

(Logo)



Transformer # 699.502 (U2044)
PRIM. 117V 60Hz BK(WH-WH)
SEC. 2x50V/10.0A BR-RD/OR-YE

(date code)

TOROID CORPORATION

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302
e-mail: sales@toroid.com * web: www.toroid.com