



DATA SHEET FOR
TRANSFORMER # 699.652

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#12/8" 0V WHITE		BROWN 0V M#13/8"
M#12/8" 117V WHITE		UO = 67.5V RMS 65V RMS / 7.4A RMS M#13/8"
		ORANGE 0V M#13/8"
		UO = 67.5V RMS 65V RMS / 7.4A RMS M#13/8"

PRIMARIES ARE INSIDE A SLEEVE.
 LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

 NOMINAL SUPPLY: 117V +/-10%
 RATED PRIMARY CURRENT: 8.9A
 RATED FREQUENCY: 60 Hz
 TEMP. RISE AT RATED LOAD: 60°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.3"	WASHER/PADS = 145mm	CORE # 800
H = 2.4"	THICKNESS = 0.08"	CORE LOSS = 3.5 W
WEIGHT = 12.4 LBS.	HOLE DIAMETER = 0.40"	NO-LOAD CURRENT = 84 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

SPEC DATE: 12/18/20 By: <i>MX/LL</i>	Label: (Logo)	 Transformer # 699.652 (U2045) PRIM. 117V 60Hz BK(WH-WH) SEC. 2x65V/7.4A BR-RD/OR-YE (date code)
---	----------------------	--

TOROID CORPORATION