



DATA SHEET FOR
TRANSFORMER # 701.062

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#23/8"
S#22/8"	117V	YELLOW		RED	6V RMS / 1.58A RMS	M#23/8"
S#22/8"	0V	ORANGE		ORANGE	0V	M#23/8"
S#22/8"	117V	BLACK		YELLOW	6V RMS / 1.58A RMS	M#23/8"

PRIMARIES ARE INSIDE A SLEEVE.
 Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 0.2/0.1A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 65°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.4"	WASHER/PADS = 50mm	CORE # 15
H = 1.2"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1BS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 2.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 12/21/20

(Logo)

Transformer # 701.062 (U2046)
 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
 Sec. 2x6V / 1.58A br-re / or-ye
 (date code)

By: *MX/LL*

(date code)

TOROID CORPORATION