



DATA SHEET FOR
TRANSFORMER # 701.222

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8" 0V	WHITE			BROWN 0V	S#22/8"
S#22/8" 117V	YELLOW			RED 22V RMS / 0.43A RMS	S#22/8"
S#22/8" 0V	ORANGE			ORANGE 0V	S#22/8"
S#22/8" 117V	BLACK			YELLOW 22V RMS / 0.43A RMS	S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.
 Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 0.2/0.1A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 57°C

<u>DIMENSIONS/WEIGHT:</u> OD = 2.4" H = 1.2" WEIGHT = 1.1BS.	<u>MOUNTING:</u> WASHER/PADS = 50mm THICKNESS = 0.04" HOLE DIAMETER = 0.17"	<u>CORE DATA:</u> CORE # 15 CORE LOSS = 0.2 W NO-LOAD CURRENT = 2.5 mA
---	--	---

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label: SPEC DATE: 12/21/20 By: <i>MX/LL</i>	Transformer # 701.222 (U2051) Prim. 2x117V 50/60Hz bk(wh-ye/or-bk) Sec. 2x22V / 0.43A br-re / or-ye (date code) (date code)
---	---

TOROID CORPORATION