

DATA SHEET FOR  
TRANSFORMER # 704.062

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHITE		BROWN	0V	M#20/8"
S#22/8"	117V	YELLOW		RED	6V RMS / 2.75A RMS	M#20/8"
S#22/8"	0V	ORANGE		ORANGE	0V	M#20/8"
S#22/8"	117V	BLACK		YELLOW	6V RMS / 2.75A RMS	M#20/8"

PRIMARIES ARE INSIDE A SLEEVE.  
 Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
 RATED PRIMARY CURRENT: 0.4/0.2A  
 RATED FREQUENCY: 50/60 Hz  
 TEMP. RISE AT RATED LOAD: 63°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1BS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 2.5 mA


Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:

SPEC DATE: 12/21/20

(Logo)

  
 Transformer # 704.062 (U2052)  
 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)  
 Sec. 2x6V / 2.75A br-re / or-ye  
 (date code)

By: *MX/LL*

(date code)

**TOROID CORPORATION**