

DATA SHEET FOR  
TRANSFORMER # 704.182

Made for STANDARD

LEADS		SCHEMATIC				LEADS	
S#22/8"	0V	WHITE			BROWN	0V	M#25/8"
S#22/8"	117V	YELLOW			RED	18V RMS / 0.92A RMS	M#25/8"
S#22/8"	0V	ORANGE			ORANGE	0V	M#25/8"
S#22/8"	117V	BLACK			YELLOW	18V RMS / 0.92A RMS	M#25/8"

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
RATED PRIMARY CURRENT: 0.4/0.2A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 65°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 2.8"	WASHER/PADS = 50mm	CORE # 30
H = 1.3"	THICKNESS = 0.04"	CORE LOSS = 0.2 W
WEIGHT = 1.1BS.	HOLE DIAMETER = 0.17"	NO-LOAD CURRENT = 2.5 mA

Dimensions stated above are nominal. Tolerance is 10%.


OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:

SPEC DATE: 09/20/18

(Logo)

By: *MX/LL*

  
Transformer # 704.182 (U2057)  
Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)  
Sec. 2x18V / 0.92A br-re / or-ye  
(date code)

(date code)

**TOROID CORPORATION**