



DATA SHEET FOR  
TRANSFORMER # 707.082

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#22/8" 0V	WHITE	BROWN 0V
S#22/8" 117V	YELLOW	RED 8.5V RMS / 3.18A RMS
S#22/8" 0V	ORANGE	ORANGE 0V
S#22/8" 117V	BLACK	YELLOW 8.5V RMS / 3.18A RMS

UO = 10.3V RMS

UO = 10.3V RMS

PRIMARIES ARE INSIDE A SLEEVE.  
 Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
 RATED PRIMARY CURRENT: 0.6/0.3A  
 RATED FREQUENCY: 50/60 Hz  
 TEMP. RISE AT RATED LOAD: 65 °C

<u>DIMENSIONS/WEIGHT:</u> OD = 3.2" H = 1.4" WEIGHT = 1.5BS.	<u>MOUNTING:</u> WASHER/PADS = 60mm THICKNESS = .05" HOLE DIAMETER = 0.20"	<u>CORE DATA:</u> CORE # 50 CORE LOSS = 0.4 W NO-LOAD CURRENT = 4.1 mA
---	---	---

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 12/21/20

(Logo)

Transformer # 707.082 (U2060)  
 Prim. 2X117V 50/60Hz bk(wh-ye/or-bk)  
 Sec. 2X8.5V / 3.18A br-re / or-ye  
 (date code)

By: *MX/LL*

(date code)

**TOROID CORPORATION**