



DATA SHEET FOR  
TRANSFORMER # 707.152

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#22/8"	0V	WHITE		BROWN	0V		M#21/8"
S#22/8"	117V	YELLOW		RED	15V RMS / 1.80A RMS	UO = 18.0V RMS	M#21/8"
S#22/8"	0V	ORANGE		ORANGE	0V	UO = 18.0V RMS	M#21/8"
S#22/8"	117V	BLACK		YELLOW	15V RMS / 1.80A RMS	UO = 18.0V RMS	M#21/8"

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
RATED PRIMARY CURRENT: 0.6/0.3A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 61 °C

DIMENSIONS/WEIGHT:  
OD = 3.2"  
H = 1.4"  
WEIGHT = 1.5BS.

MOUNTING:  
WASHER/PADS = 60mm  
THICKNESS = .05"  
HOLE DIAMETER = 0.20"

CORE DATA:  
CORE # 50  
CORE LOSS = 0.4 W  
NO-LOAD CURRENT = 4.1 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 12/21/20

(Logo)

Transformer # 707.152 (U2063)  
Prim. 2X117V 50/60Hz bk(wh-ye/or-bk)  
Sec. 2X15V / 1.80A br-re / or-ye  
(date code)

By: *MX/LL*

(date code)

**TOROID CORPORATION**