



DATA SHEET FOR  
TRANSFORMER # 711.152

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"	0V	WHTIE		BROWN	0V	M#19/8"
S#22/8"	117V	YELLOW		RED	15V RMS / 3.0A RMS	M#19/8"
S#22/8"	0V	ORANGE		ORANGE	0V	M#19/8"
S#22/8"	117V	BLACK		YELLOW	15V RMS / 3.0A RMS	M#19/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
 RATED PRIMARY CURRENT: 1.0/0.5A  
 RATED FREQUENCY: 50/60 Hz  
 TEMP. RISE AT RATED LOAD: 61 °C

DIMENSIONS/WEIGHT:  
 OD = 3.9"  
 H = 1.5"  
 WEIGHT = 2.2 LBS.

MOUNTING:  
 WASHER/PADS = 70mm  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.25"

CORE DATA:  
 CORE # 900095  
 CORE LOSS = 0.6 W  
 NO-LOAD CURRENT = 5.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label: Transformer # 711.152 (U2070)  
 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)  
 Sec. 2x15V / 3.0A br-re/or-ye  
 (date code)

SPEC DATE: 12/21/20

By: *MX/LL*

**TOROID CORPORATION**