

DATA SHEET FOR
TRANSFORMER # 711.152

Made for STANDARD

LEADS		SCHEMATIC				LEADS	
S#22/8"	0V	WHTIE			BROWN	0V	M#19/8"
S#22/8"	117V	YELLOW			RED	15V RMS / 3.0A RMS	M#19/8"
S#22/8"	0V	ORANGE			ORANGE	0V	M#19/8"
S#22/8"	117V	BLACK			YELLOW	15V RMS / 3.0A RMS	M#19/8"


PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 1.0/0.5A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 61 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70mm	CORE # 900095
H = 1.5"	THICKNESS = 0.05"	CORE LOSS = 0.6 W
WEIGHT = 2.2 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 5.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 711.152 (U2070)
 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
 Sec. 2x15V / 3.0A br-re/or-ye
 (date code)

SPEC DATE: 09/20/18

By: *MX/LL*

TOROID CORPORATION