

DATA SHEET FOR
TRANSFORMER # 711.182

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#22/8"	0V	WHITE			BROWN	0V	M#19/8"
S#22/8"	117V	YELLOW			RED	18V RMS / 2.50A RMS	M#19/8"
S#22/8"	0V	ORANGE			ORANGE	0V	M#19/8"
S#22/8"	117V	BLACK			YELLOW	18V RMS / 2.50A RMS	M#19/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 1.0/0.5A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 54 °C


DIMENSIONS/WEIGHT:
 OD = 3.9"
 H = 1.5"
 WEIGHT = 2.2 LBS.

MOUNTING:
 WASHER/PADS = 70mm
 THICKNESS = 0.05"
 HOLE DIAMETER = 0.25"

CORE DATA:
 CORE # 900095
 CORE LOSS = 0.6 W
 NO-LOAD CURRENT = 5.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 711.182 (U2071)
 SPEC DATE: 12/21/20 PRI. 2x117V 50/60Hz BK(WH-YE/OR-BK)
 (Logo) SEC. 2x18V/2.50A BR-BR/OR-YE
 By: *MX/LP* (date code)

TOROID CORPORATION