



DATA SHEET FOR
TRANSFORMER # 713.182

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#24/8" 0V	WHITE	M#17/8"
M#24/8" 117V	YELLOW	M#17/8"
M#24/8" 0V	ORANGE	M#17/8"
M#24/8" 117V	BLACK	M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.
 Primaries must be connected together in series or in parallel.
 LEADS: M=Magnet wire self leads.Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 1.4/0.7A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 59°C

<u>DIMENSIONS/WEIGHT:</u> OD = 3.9" H = 1.9" WEIGHT = 3.0 LBS.	<u>MOUNTING:</u> WASHER/PADS = 70mm THICKNESS = .05" HOLE DIAMETER = 0.25"	<u>CORE DATA:</u> CORE # 900140 CORE LOSS = 0.9 W NO-LOAD CURRENT = 8.7 mA
---	---	---

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 12/21/20

(Logo)

Transformer # 713.182 (U2078)
 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
 Sec. 2x18V / 3.89A br-re / or-ye
 (date code)

By: *MX / LL*

(date code)

TOROID CORPORATION