



DATA SHEET FOR  
TRANSFORMER # 767.1202

Made for STANDARD

| <u>LEADS</u> |      | <u>SCHEMATIC</u> |  |        |                      | <u>LEADS</u> |  |
|--------------|------|------------------|--|--------|----------------------|--------------|--|
| M#17/8"      | 0V   | WHITE            |  | BROWN  | 0V                   | M#17/8"      |  |
| M#17/8"      | 117V | YELLOW           |  | RED    | 117V RMS / 2.86A RMS | M#17/8"      |  |
| M#17/8"      | 0V   | ORANGE           |  | ORANGE | 0V                   | M#17/8"      |  |
| M#17/8"      | 117V | BLACK            |  | YELLOW | 117V RMS / 2.86A RMS | M#17/8"      |  |

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%  
RATED PRIMARY CURRENT: 6.0/3.0A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 52°C

|                           |                       |                         |
|---------------------------|-----------------------|-------------------------|
| <u>DIMENSIONS/WEIGHT:</u> | <u>MOUNTING:</u>      | <u>CORE DATA:</u>       |
| OD = 6.3"                 | WASHER/PADS = 145mm   | CORE # 900673           |
| H = 2.3"                  | THICKNESS = 0.08"     | CORE LOSS = 2.3 W       |
| WEIGHT = 10.9 LBS.        | HOLE DIAMETER = 0.32" | NO-LOAD CURRENT = 29 mA |

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 09/20/18

(Logo)

Transformer # 767.1202 (U2118)  
Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)  
Sec. 2x117V / 2.86A br-re / or-ye  
(date code)

By: *MX / LL*

(date code)

**TOROID CORPORATION**