



DATA SHEET FOR
TRANSFORMER # 802.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#20/8" 0V S#20/8" 120V		WHITE 0V A/R THERMAL SWITCH 120°C UO = 127.2V RMS BLACK 120V RMS / 200VA GRN/YEL STATIC SHIELD
		S#20/8" S#20/8" S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.
 LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
 RATED PRIMARY CURRENT: 1.81A
 RATED FREQUENCY: 60 Hz
 TEMP. RISE AT RATED LOAD: 46 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90mm	CORE # 900225
H = 1.9"	THICKNESS = 0.06"	CORE LOSS = 1.2 W
WEIGHT = 4.1 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 25 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

	Label:	
SPEC DATE: 12/17/20	Transformer # 802.1201 INPUT: 120V 60Hz OUTPUT: 120V/200VA STATIC SHIELD P/N B01319718	SLEEVE (WHT-BLK) WHT-BLK GRN/YEL
By: <i>mx</i>	(Logo)	(date code)

TOROID CORPORATION