



DATA SHEET FOR
TRANSFORMER # 803.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#20/8" 0V WHITE		S#20/8"	
S#20/8" 120V BLACK		S#20/8"	
		WHITE 0V A/R THERMAL SWITCH 120°C UO = 125.0V RMS	S#20/8"
		BLACK 120V RMS / 300VA	S#22/8"
	GRN/YEL STATIC SHIELD		

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 2.67A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 47 °C

<u>DIMENSIONS/WEIGHT:</u> OD = 4.5" H = 2.5" WEIGHT = 5.8 LBS.	<u>MOUNTING:</u> WASHER/PADS = 90mm THICKNESS = 0.06" HOLE DIAMETER = 0.25"	<u>CORE DATA:</u> CORE # 900330 CORE LOSS = 1.7 W NO-LOAD CURRENT = 37 mA
---	--	--

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

SPEC DATE: 12/17/20 By: <i>mx</i>	Label: (Logo)	Transformer # 803.1201 INPUT: 120V 60Hz OUTPUT: 120V/300VA STATIC SHIELD P/N B01319719 (date code)	SLEEVE (WHT-BLK) WHT-BLK GRN/YEL
--	----------------------	---	--

TOROID CORPORATION