



DATA SHEET FOR  
TRANSFORMER # 810.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#14/8"      0V S#14/8"      120V		WHITE      0V A/R THERMAL SWITCH 120°C UO = 122.6V RMS BLACK      120V RMS / 1000VA GRN/YEL    STATIC SHIELD
		S#14/8" S#14/8" S#18/8"

PRIMARIES ARE INSIDE A SLEEVE.  
 LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            120V +/-10%  
 RATED PRIMARY CURRENT: 8.65A  
 RATED FREQUENCY:        60 Hz  
 TEMP. RISE AT RATED LOAD: 50 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.4"	WASHER/PADS = 145mm	CORE # 1000
H = 3.1"	THICKNESS = 0.08"	CORE LOSS = 4.4 W
WEIGHT = 14.8 LBS.	HOLE DIAMETER = 0.40"	NO-LOAD CURRENT = 96 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

	Label:	
SPEC DATE: 12/17/20	Transformer # 810.1201	
	INPUT: 120V 60Hz	SLEEVE (WHT-BLK)
	OUTPUT: 120V/1000VA	WHT-BLK
	STATIC SHIELD	GRN/YEL
	P/N B01319723	
By: <i>mx</i>	(Logo)	(date code)

**TOROID CORPORATION**