

DATA SHEET FOR
TRANSFORMER # 815.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#12/8" 0V WHITE		S#12/8"	
S#12/8" 120V BLACK		S#12/8"	
		WHITE 0V A/R THERMAL SWITCH 120°C UO = 122.3V RMS	S#12/8"
		BLACK 120V RMS / 1500VA	S#16/8"
	GRN/YEL STATIC SHIELD		


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 12.90A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 53 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 7.2"	POTTED CENTER	CORE # 901434
H = 3.5"	FLAT BOTTOM	CORE LOSS = 5.8 W
WEIGHT = 21.5 LBS.	HOLE DIAMETER = 3/8"	NO-LOAD CURRENT = 126 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

SPEC DATE: 12/17/20 By: <i>mx</i>	Label: (Logo)	Transformer # 815.1201 INPUT: 120V 60Hz OUTPUT: 120V/1500VA STATIC SHIELD P/N B01319724 (date code)	 SLEEVE (WHT-BLK) WHT-BLK GRN/YEL
--	----------------------	--	---

TOROID CORPORATION