



DATA SHEET FOR
TRANSFORMER # 820.1201

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#10/8" 0V WHITE		S#10/8"
S#10/8" 120V BLACK		A/R THERMAL SWITCH 120°C UO = 121.9V RMS
		120V RMS / 2000VA
		GRN/YEL STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 17.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 55 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 8.3"	POTTED CENTER	CORE # 2000
H = 3.8"	FLAT BOTTOM	CORE LOSS = 8.1 W
WEIGHT = 27.6 LBS.	HOLE DIAMETER = 0.50"	NO-LOAD CURRENT = 175 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

SPEC DATE: 12/17/20 By: <i>mx</i>	Label: (Logo)	Transformer # 820.1201 INPUT: 120V 60Hz OUTPUT: 120V/2000VA STATIC SHIELD P/N B01319725 (date code)	 SLEEVE (WHT-BLK) WHT-BLK GRN/YEL
--	----------------------	--	--

TOROID CORPORATION