



DATA SHEET FOR
TRANSFORMER # 830.1201

Made for STANDARD

page 1 of 1

LEADS	SCHEMATIC	LEADS
S#10/12" 0V S#10/12" 120V S#16/12" *A/R THERMAL SWITCH 120°C/6.0A S#16/12"		WHITE 0V BLACK 120V RMS / 3000VA GRN/YEL STATIC SHIELD S#10/12" S#10/12" S#14/12"

PRIMARIES ARE INSIDE A SLEEVE.
 LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.
 *THERMAL SWITCH FOR CONTROL CIRCUIT ONLY. MAXIMUM CURRENT IS 6.0A.

NOMINAL SUPPLY: 120V +/-10% RATED PRIMARY CURRENT: 25.7A RATED FREQUENCY: 60 Hz TEMP. RISE AT RATED LOAD: 51 °C	<u>MOUNTING:</u> POTTED CENTER FLAT BOTTOM HOLE DIAMETER = 0.50"	<u>CORE DATA:</u> CORE # 903200 CORE LOSS = 10.8 W NO-LOAD CURRENT = 234 mA
--	---	--

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to AAMI ES60601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

Label: SPEC DATE: 12/17/20 By: <i>mx</i>	Transformer # 830.1201 INPUT: 120V 60Hz OUTPUT: 120V/3000VA STATIC SHIELD P/N B01319727 (Logo)	SLEEVE (WHT-BLK) WHT-BLK GRN/YEL (date code)
--	---	---

TOROID CORPORATION