



DATA SHEET FOR  
TRANSFORMER # 901.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#22/12"	0V	WHITE		WHITE	0V	S#22/12"
S#22/12"	100V	BLUE		A/R THERMAL FUSE 120° C	UO = 138.7V RMS	S#22/12"
S#22/12"	120V	YELLOW		BLACK	120V RMS / 100VA	S#22/12"
S#22/12"	0V	ORANGE		VIOLET	STATIC SHIELD	S#22/12"
S#22/12"	100V	RED				
S#22/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 1.2/1.0/0.6/0.5A  
 RATED FREQUENCY: 50/60Hz  
 TEMP. RISE AT RATED LOAD: 60° C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70 mm.	CORE # 900115
H = 1.8"	THICKNESS = 0.05"	CORE LOSS = 0.7 W
WEIGHT = 2.5 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 6.4 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized UL 2601-1, AAMI ES60601-1 and CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:   
 Transformer # B04316190 (901.1201)  
 Input Volt: 100/120/200/220/240V  
 Input Current: 1.2/1.0/0.6/0.6/0.5A

SPEC DATE: 06/24/15

(Logo)

By: *mx* (date code)

**TOROID CORPORATION**