



DATA SHEET FOR
TRANSFORMER # 902.1201

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#22/12"	0V	WHITE		WHITE	0V		S#22/12"	
S#22/12"	100V	BLUE					A/R THERMAL FUSE 120° C	S#22/12"
S#22/12"	120V	YELLOW			BLACK	120V RMS / 200VA		S#22/12"
S#22/12"	0V	ORANGE			VIOLET	STATIC SHIELD		S#22/12"
S#22/12"	100V	RED						
S#22/12"	120V	BLACK						

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 2.2/1.9/1.0/0.9A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 63° C

DIMENSIONS/WEIGHT:
 OD = 4.5"
 H = 2.1"
 WEIGHT = 4.3 LBS.

MOUNTING:
 WASHER/PADS = 90 mm.
 THICKNESS = 0.06"
 HOLE DIAMETER = 0.25"

CORE DATA:
 CORE # 900225
 CORE LOSS = 1.2 W
 NO-LOAD CURRENT = 10.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:		
SPEC DATE: 04/09/21		Transformer # B04316191 (902.1201)
		Input Volt: 100/120/200/220/240V
		Input Current: 2.3/1.9/1.2/1.1/1.0A
By: <i>mx</i>	(Logo)	(date code)

TOROID CORPORATION