



DATA SHEET FOR
TRANSFORMER # 903.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#22/12"	0V	WHITE		BROWN	0V	S#22/12"	
S#22/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#22/12"	120V	YELLOW		UO = 130.5V RMS	RED	120V RMS / 150VA	S#22/12"
S#22/12"	0V	ORANGE			ORANGE	0V	S#22/12"
S#22/12"	100V	RED		A/R THERMAL FUSE 120°C	YELLOW	120V RMS / 150VA	S#22/12"
S#22/12"	120V	BLACK			VIOLET	STATIC SHIELD	S#22/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 3.3/2.8/1.5/1.4A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 57°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.6"	WASHER/PADS = 110mm	CORE # 900370
H = 2.3"	THICKNESS = 0.08"	NO-LOAD LOSS = 1.7 W
WEIGHT = 6.0 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD AMPS = 16 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.



Label: Transformer # B04315236 (903.1202)
 Input Volt: 100/120/200/220/240V
 Input Current: 3.3/2.8/1.7/1.5/1.4A

SPEC DATE: 04/09/21

(Logo)

By: *MX* (date code)

TOROID CORPORATION