



DATA SHEET FOR
TRANSFORMER # 903.1202

Made for STANDARD

LEADS	SCHEMATIC	LEADS
S#22/12" 0V	WHITE	BROWN 0V
S#22/12" 100V	BLUE	A/R THERMAL FUSE 120°C UO = 130.5V RMS
S#22/12" 120V	YELLOW	RED 120V RMS / 150VA
S#22/12" 0V	ORANGE	ORANGE 0V
S#22/12" 100V	RED	A/R THERMAL FUSE 120°C UO = 130.5V RMS
S#22/12" 120V	BLACK	YELLOW 120V RMS / 150VA
		VIOLET STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 3.3/2.8/1.5/1.4A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 57°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.6"	WASHER/PADS = 110mm	CORE # 900370
H = 2.3"	THICKNESS = 0.08"	NO-LOAD LOSS = 1.7 W
WEIGHT = 6.0 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD AMPS = 16 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: SPEC DATE: 12/17/20 (Logo) By: <i>MX</i>	Transformer # B04315236 (903.1202) Input Volt: 100/120/200/220/240V Input Current: 3.3/2.8/1.7/1.5/1.4A (date code)	
--	---	--

TOROID CORPORATION