



DATA SHEET FOR
TRANSFORMER # 906.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#18/12"	0V	WHITE		WHITE	0V	S#18/12"
S#18/12"	100V	BLUE		A/R THERMAL FUSE 120° C	UO = 127.9V RMS	S#18/12"
S#18/12"	120V	YELLOW		BLACK	120V RMS / 600VA	S#18/12"
S#18/12"	0V	ORANGE		VIOLET	STATIC SHIELD	S#20/12"
S#18/12"	100V	RED				
S#18/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 6.4/5.4/3.0/2.7A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 64° C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.5"	WASHER/PADS = 145 mm.	CORE # 900639
H = 2.5"	THICKNESS = 0.08"	CORE LOSS = 3.1 W
WEIGHT = 10.4 LBS.	HOLE DIAMETER = 0.40"	NO-LOAD CURRENT = 27.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. RoHS compliant. Leakage current < 100µA.

Label:
 Transformer # B04316194 (906.1201)
 Input Volt: 100/120/200/220/240V
 Input Current: 6.5/5.4/3.3/3.0/2.7A

SPEC DATE: 04/09/21

(Logo) (date code)

By: *mx*

TOROID CORPORATION